

## → 352F PROFESSIONAL SERIES TABLETOP FOLDER

dual roller friction feed system accepts a wide variety of stocks, including carbonless sheets | adjusts in seconds for standard and custom folds | variable speed control | powered exit conveyor | sheet separation from top of fanned stack | polyurethane foam rollers eliminate the need for fold roller pressure settings | heavy-duty, non-flexing side frames | needle bearings for high speed production | optional extended delivery system, crossfold for right-angle folding, and slitting, scoring, and perforating attachments

Dimensions (D x W x H): 22 ¼ x 41 ¾ x 14 ½ inches, Shipping weight: 105 lbs.



### DUAL FEED ROLLERS



The dual roller feed system folds a wide range of stock.

### POWERED CONVEYOR



A powered exit conveyor ensures smooth ejection of folded paper.

### → 352F

Speed	22,000 sheets/hr*
Paper size	2" x 2 ¼" to 14" x 21 ¼"
Paper weight	13 to 110 lbs.*
Sheet capacity	300*
Power supply	115 V, 60 Hz

\* may vary due to variations in paper and power supply

Dealer: **AUTOMATED BUSINESS MACHINES, INC.**

6073 NW 167th Street, Suite C-24  
Miami, FL 33015-4347  
[www.abmmiami.com](http://www.abmmiami.com)

(305) 620-0020 • (954) 739-1222  
(561) 833-9044 • (800) 446-5501  
fax (305) 620-2201 • [sales@abmmiami.com](mailto:sales@abmmiami.com)

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
[www.mbmcorp.com](http://www.mbmcorp.com)

**IDEAL.MBM**  
CORPORATION

1675 Sismet Road, unit 4  
Mississauga, Ontario L4W 4K8  
800-387-2528, fax: 905-840-1114  
[www.ideal-mbm.com](http://www.ideal-mbm.com)

All technical data is approximate and subject to change. © MBM Corporation, 2/2008.