

Triumph®

by IDEAL


→ TRIUMPH 4850

AUTOMATIC CUTTER · electric blade and clamp drive · automatic clamp can be lowered or raised independently from blade · spindle-guided back gauge with calibrated crank · precision back gauge measuring scale on front table · optical cutting line · dual side guides on front and rear tables · solid steel blade carrier · stand with storage shelf · **SAFETY FEATURES:** external blade depth adjustment · two-hand operation · transparent safety guards on front and rear tables · automatic blade and clamp return from any position · disc brake for instant blade stop · safety lock with key and main switch

Dimensions (D x W x H): 38 1/4 x 29 3/4 x 48 1/2 inches, Shipping weight: 556 lbs.



OPTICAL CUTTING LINE



An optical cutting line indicates exact location of cut and helps to perfectly position trim marks.

REAR SAFETY GUARD



The transparent rear safety guard gives a clear view of side guides and back gauge.

→ TRIUMPH 4850

Cutting width	18 7/8"
Cutting height	3"
Narrow cut	1 1/4"
Cutting length behind blade	17 1/4"
Table length in front of blade	13 5/8"
Motor	2 hp
Power supply	115 V, 60 Hz*

* 20 amp dedicated line required

Dealer: **AUTOMATED BUSINESS MACHINES, INC.**

6073 NW 167th Street, Suite C-24

Miami, FL 33015-4347

www.abmmiami.com

(305) 620-0020 • (954) 739-1222

(561) 833-9044 • (800) 446-5501

fax (305) 620-2201 • sales@abmmiami.com

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1 Regan Road, unit 12
Brampton, Ontario L7A 1B8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com

All technical data is approximate and subject to change. © MBM Corporation, 10/2006.